




101STR.1.02-R868



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.  
Circular design in diameter 150mm.  
Protection rating against dust and moisture: IP54 from underneath.  
White painted aluminium reflector. Sandblasted metalized aluminium reflector available as option.  
Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request.  
Intermediate tempered frosted glass .  
Remote driver supplied.  
Electronic options for lighting control: DALI-2.  
3 hours battery available as option (class I).  
Passive temperature management: heat dissipation flows through aluminium heat sink.  
Ceiling-mounted by spring clamps for easy installation.

**Luminaire luminous flux:** 1071lm  
**Luminaire connected power:** 12.61 W  
**Luminaire efficiency:** 85 lm/W  
**Light source luminous flux:** 1815lm  
**Light source power:** 11 W  
**Constant Current:** 350 mA  
**CRI:** >90  
**Colour Temperature:** 4000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 65°  
**LOR:** 59%  
**Average Service Life:** 50000h  
**LED reliability:** 50000h L90B10  
**UGR:** 19 under the below indicated parameters  
Room dimensions X=4H/8H  
Reflectance 20% | 50% | 70%  
Luminaire spacing = 0.5m  
**Photobiological safety group:** 1  
**Cd/Klm:** 819  
**This product contains a light source of energy efficiency class E**



**Electronic Equipment**

**K:** On/Off (basic)  
**S:** On/Off (AC/DC + looping through)  
**SE:** On/Off (AC/DC+looping) + 3h battery  
**D:** DALI-2/switchDIM/corridorFUNCTION  
**DE:** DALI-2/switchDIM/corridorFUNCTION + Battery 3h  
**B:** Bluetooth-Casambi

\*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

**Finishes**

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

**Upgradeable, Replaceable, Repairable**



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346  
BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**  
Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarra  
08540 Centelles | Barcelona  
Spain

**Contact**  
T. +34 93 881 35 12 info@rovasi.com  
T. +34 93 881 37 13 [www.rovasi.com](http://www.rovasi.com)