



103VTN.1-R864



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Circular design with trimless appearance in diameter 150mm.

Powder painted aluminium circle and interior trim available in various finishes, customized RAL under request. To complete the effect of this fixture, it is also recommended that the inner ring should be painted the same RAL colour as the ceiling.

Facetted metalized aluminium reflector.

Glass accessory available to increase the protection rating to IP54 | IK05 from underneath [reference M2.B0150].

Remote driver supplied.

Electronic options for lighting control: DALI-2.

3 hours battery available as option (class I).

Passive temperature management: heat dissipation flows through aluminium heat sink.

Ceiling-mounted using galvanised steel support with screws.

Luminaire luminous flux: 1816lm

Luminaire connected power: 12.61 W

Luminaire efficiency: 144 lm/W

Light source luminous flux: 2040lm

Light source power: 11 W

Constant Current: 350 mA

CRI: >80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 40°

LOR: 89%

Average Service Life: 50000h

LED reliability: 50000h L90B10


UGR: <19

Photobiological safety group: 1

Cd/Klm: 1631

Imax: 3327 Cd

This product contains a light source of energy efficiency class D



Electronic Equipment

K: On/Off (basic)

S: On/Off (AC/DC + looping through)

SE: On/Off (AC/DC+looping) + 3h battery

D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM/corridorFUNCTION + Battery 3h

B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 03.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12
T. +34 93 881 37 13

info@rovasi.com

www.rovasi.com