





WATERTIGHT SQ

IP65 Recessed downlights

ROVASI
Positive Lighting



101WSQ.8.01-I869



Recessed ceiling-mounted downlight with symmetrical light distribution.

Square design in 258mm x 258mm.

Protection rating against dust and moisture: entire IP65.

Protection rating of resistance to harmful mechanical impacts: IK07.

High purity matt anodised aluminium reflector.

5mm tempered protection glass clear as standard, other finishes under request.

Polycarbonate diffuser as option to achieve IK10 protection degree.

Die-cast aluminium body treated against corrosion and coated with polyester powder painting.

Frame made of 316L stainless steel marine grade.

A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws [reference F2.A0258+F2.A1].

Temperature resistant silicone rubber gasket.

Anti-condensation device.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flow through the fixture body itself.

Mounted to the ceiling by four fixing points.

Pre-wiring of 35cm cable 3x1mm².

IP68 connector to be ordered separately [reference F3.A3 (On/Off) / F3.A5 (DALI)].

Luminaire luminous flux: 2039lm

Luminaire connected power: 18.33 W

Luminaire efficiency: 111 lm/W

Light source luminous flux: 2755lm

Light source power: 17 W

Constant Current: 500 mA

CRI: >80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 72°

LOR: 74%

Average Service Life: 50000h


LED reliability: 50000h L90B10

Photobiological safety group: 1

Cd/Klm: 616

Imax: 1697 Cd

This product contains a light source of energy efficiency class D



Electronic Equipment

S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **8:** Stainless Steel 316L: Marine grade, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 11.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12
T. +34 93 881 37 13

info@rovasi.com
www.rovasi.com