




## 736KTA.1-I809



Wall mounted linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting. Double light emission: up and down.  
 Linear fixture in 1408mm length and in a width of 44mm.  
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.  
 PMMA optics for controlling and directing the light.  
 Highly efficient linear printed circuit board.  
 Accessories available to create customized linear systems.  
 Built-in driver, included.  
 Electronic options for lighting control: DALI-2 (for downlight position only) .  
 3 hours battery available as option.  
 Passive temperature management.  
 Wall mounted by mounting brackets.  
 Other options available:  
 Recessed.  
 Frameless recessed.  
 Pendant.  
 Surface mounted.  
 Projectors.  
 >It is possible to combine different lengths and junction modules in different ways to create customized design.



**Luminaire luminous flux:** 2925lm  
**Luminaire connected power:** 17.76 W  
**Luminaire efficiency:** 165 lm/W  
**Light source luminous flux:** 3145lm  
**Light source power:** 16 W  
**Constant Current:** 150 mA  
**CRI:** 80  
**Colour Temperature:** 4000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 43°  
**LOR:** 93%  
**Average Service Life:** 50000h  
**LED reliability:** >60000h L80B10  
**UGR:** <19 under the below indicated parameters  
 Room dimensions X=4H/8H  
 Reflectance 20% | 50% | 70%  
 Luminaire spacing = 0.3m  
**Photobiological safety group:** 1  
**Cd/Klm:** 704  
**Imax:** 2214 Cd  
**This product contains a light source of energy efficiency class C**


**Electronic Equipment**

**S:** On/Off  
**SE:** On/Off + 3h battery  
**D:** DALI-2/switchDIM (only downlight position)  
**DE:** DALI-2/switchDIM+ 3 hours battery  
**DDE:** DALI-2/switchDIM+ 3 hours battery (DALI)

\*Add the suffix **-S, -SE, -D, -DE, -DDE** after the reference to indicate your electronic equipment choice.

**Finishes**

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

**Upgradeable, Replaceable, Repairable**

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 04.05.2024]

**5 years guarantee**

BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

**ROVASI S.L.**

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

**Contact**

T. +34 93 881 35 12    info@rovasi.com  
 T. +34 93 881 37 13    **www.rovasi.com**