

521HRN.1-I979



IP20


650°



3.16Kg

Pendant linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Double light emission: up and down.
Linear fixture in 576mm length and in a width of 50mm.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
Range of PMMA optics to achieve specific photometric results.
Highly efficient linear printed circuit board.
Accessories available to create customized linear systems.
Built-in driver, separate switching up and down.
Electronic options for lighting control: DALI-2 (for downlight position only).
Passive temperature management.
Ceiling-mounted with adjustable steel wire suspension (1 m) and transparent electrical wire. Different suspension length on request.
It is possible to combine different lengths and junction modules in different ways to create customized design.

Luminaire luminous flux: 1445lm
Luminaire connected power: 13.88 W
Luminaire efficiency: 104 lm/W
Light source luminous flux: 1490lm
Light source power: 10 W
Constant Current: 350 mA
CRI: 90
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 31°
LOR: 97%
Average Service Life: 50000h
LED reliability: >54000h L80B10
UGR: <19
Photobiological safety group: 1
Cd/Klm: 2060
Imax: 3069 Cd
This product contains a light source of energy efficiency class D



Electronic Equipment

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 07.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com