


101SSQ.1.01-R619



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent.
Passive temperature management: heat dissipation flows through an aluminium heat sink.
Ceiling-mounted by spring clamps for easy installation.

Luminaire luminous flux: 670lm
Luminaire connected power: 7.69 W
Luminaire efficiency: 87 lm/W
Light source luminous flux: 670lm
Light source power: 6.6 W
Constant Current: 200 mA
CRI: >90
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 24°
LOR: 100%
Average Service Life: 50000h
LED reliability: >50000h L70B50
UGR: <16
Photobiological safety group: 1
Cd/Klm: 3746
Imax: 2510 Cd
This product contains a light source of energy efficiency class F



Electronic Equipment


K: On/Off (basic)
S: On/Off (AC/DC)
SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION
DE: DALI-2/switchDIM + 3h battery
B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 05.05.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com